



SPLVDS031RH

Quad LVDS Line Driver

ORDERING INFORMATION

ORDER NUMBER	DESCRIPTION
SPLVDS031RH-EM	Engineering Model (EM)
SPLVDS031RH-QM	Qualification Model (QM)
SPLVDS031RH-FM	Flight Model (FM)

QUALITY LEVELS

SYMBOL	EM	QM	FM ¹⁾
Wafer selection			■
WLAT including SEM, TID and lifetime tests			■
Ceramic dual in-line FP-16 package	■	■	■
Internal visual inspection according to ESCC 2049000		■	■
Hermetically sealed		■	■
Electrical test @ room temperature	■	■	■
Electrical test @ low and high temperature		■	■
Screening according to ESCC 9000		□ ²⁾	■
Lot failure checks according to ESCC 9000			■
Production lot validation testing (LAT) according to ESCC 9000			■
Customer pre-cap inspection possible			□
Data package available for order			□
Dedicated tests available on request			□
Parts selection available for order			□

¹⁾ For Flight Models the related Procurement Specification is relevant only.

²⁾ Partial screening. Full screening available for order.

INTENDED USE

The SPLVDS031RH is a radiation hardened high-reliability integrated circuit for space applications. It comes in a hermetic ceramic power flatpack 16. The device can be ordered in 3 quality levels - EM, QM and FM:

Engineering Models (EM) are basically electrically tested. They are for evaluation purposes only and are NOT suitable for qualification of modules or for flight missions. Engineering Models are sold „AS IS“ with no warranty of full datasheet compliance.

Qualification Models (QM) are screened for datasheet compliance. They are intended for qualification of modules but are NOT suitable for flight missions.

Flight Models (FM) are qualification tested and intended for flight missions. They are compliant with the SPLVDS031RH Procurement Specification.

PACKING

- The SPLVDS031RH in flatpack 16 are individually inserted in protective plastic carriers.
- The devices in the carriers are inserted in ESD protective plastic bags which are marked with an ESD warning imprint and labelled with the respective device serial number.
- The devices in the ESD bags are packed and delivered in sealed shipping boxes with antistatic foam.

HANDLING PRECAUTIONS

The SPLVDS031RH is susceptible to damage by improper handling:

- Although the SPLVDS031RH features ESD protection circuitry, permanent damage may occur on devices subjected to high energy ESD. Do not unbag or handle the device without proper ESD precautions applied.
- Take care when removing the device from the protective plastic carrier to avoid bending of the leads and mechanical damage.

IMPORTANT NOTICE

The information contained in this document is believed to be accurate at the time of printing. SPACE IC reserves the right to make changes to its products or specifications without notice, however, and assumes no responsibility or liability for the use of its products; nor does the purchase, lease, or use of a product or service from SPACE IC convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of SPACE IC or of third parties. Please visit our website for the most recent revision of this datasheet or contact info@space-ic.com. Customers are responsible for their products and applications using SPACE IC products.

Resale of SPACE IC products or services with statements different from or beyond the parameters stated by SPACE IC for that product or service voids all express and any implied warranties for the associated SPACE IC product or service. SPACE IC is not responsible or liable for any such statements.

© 2020 SPACE IC GmbH. All rights reserved. Information and data in this document are owned by SPACE IC and may not be edited, reproduced or redistributed in any way without written consent from SPACE IC.